

## MAXVU



The new MAXVU is a cost effective temperature controller which is fast to configure, has improved display visibility and reduces costs by minimizing wiring and panel space.

## At-a-Glance

### Save Valuable Time - Set-Up in Under 60 Seconds

MAXVU has been specially designed for ease of use with a basic setup menu accessed from the front keypad.

- Includes 10 most common parameter settings
- Set-up in less than 60 sec for many applications
- Advanced set-up menu can also be accessed when needed

Alternatively fast configuration of multiple instruments can be achieved with the easy-to-use MAXVU PC Software.



### Improve Process Monitoring with a High Visibility Display

The high visibility display provides increased clarity and enables vital process information and alarm messages to be viewed at a glance, even from a distance.

MAXVU's impressive large digits create the largest active display area for any 1/16DIN (48x48mm) controller and is equally impressive on the larger 1/8DIN version (96 x48mm).

MAXVU16




MAXVU8



### Reduce Space Required Behind-the-Panel

The short 67mm depth benefits installers by giving better access and reducing the panel depth required.

This results in MAXVU being easier to wire and quicker to install to save in overall costs.



# Key Features

## CONTROL

MAXVU:

- PID or ON-OFF control
- 'Heat' only or 'heat & cool' strategy
- 2 alarms (absolute, deviation, band, loop)
- Latching or non-latching alarm outputs
- 1 or 2 point calibration
- Ramp/dwell with delay time
- Reset to defaults

## INPUTS

- Thermocouple: B, C, J, K, L, N, R, S, T,
- RTD: PT100 2 or 3 wire,
- Linear ranges: 0/4 to 20mA, 0/1 to 5V, 0/2 to 10V

## OUTPUTS

2 or 3 outputs; relay or SSR

## INDICATORS

MAXVU: Output status

## DISPLAY

1/16 DIN: 18mm upper, 10.2mm lower  
1/8 DIN: 18mm upper, 18mm lower

## COMMS

RS485 Modbus RTU  
Integral configuration port

## PROGRAMMING

Front keys or software programming

## FACIA & KEYPAD

3 tactile keys



# MAXVU Configuration Software

Controllers can be programmed quickly using the dedicated PC configuration tool via MAXVU's integral configuration port.

- Logical menu driven interface
- Tables with dropdown menus
- Graphical setup wizard with informative help panel
- Save configuration files
- Print report of controller settings



## Ordering Code

<p><b>MV</b>   <b>16</b>   <b>0</b>   <b>M</b>   <b>AA0</b>   <b>0</b>   <b>2</b>   <b>1</b>   <b>U0</b></p> <p><b>Format</b> 16 1/16 DIN, 48 x 48mm 08 1/8 DIN, 96 x 48mm</p>	<p><b>Supply Voltage</b> M 110 to 240V AC L 24V AC / DC</p>	<p><b>Communications</b> 0 Not Fitted C RS485 Communications</p>																												
<p><b>Output</b></p> <table border="0"> <tr> <td></td> <td>Out 1</td> <td>Out 2</td> <td>Out 3</td> </tr> <tr> <td>AA0</td> <td>SSR</td> <td>SSR</td> <td>None</td> </tr> <tr> <td>AR0</td> <td>SSR</td> <td>Relay</td> <td>None</td> </tr> <tr> <td>RR0</td> <td>Relay</td> <td>Relay</td> <td>None</td> </tr> <tr> <td>AAR</td> <td>SSR</td> <td>SSR</td> <td>Relay</td> </tr> <tr> <td>ARR</td> <td>SSR</td> <td>Relay</td> <td>Relay</td> </tr> <tr> <td>RRR</td> <td>Relay</td> <td>Relay</td> <td>Relay</td> </tr> </table>		Out 1	Out 2	Out 3	AA0	SSR	SSR	None	AR0	SSR	Relay	None	RR0	Relay	Relay	None	AAR	SSR	SSR	Relay	ARR	SSR	Relay	Relay	RRR	Relay	Relay	Relay		
	Out 1	Out 2	Out 3																											
AA0	SSR	SSR	None																											
AR0	SSR	Relay	None																											
RR0	Relay	Relay	None																											
AAR	SSR	SSR	Relay																											
ARR	SSR	Relay	Relay																											
RRR	Relay	Relay	Relay																											

## Flexible for Use in a Range of Applications

MAXVU provides an affordable solution for applications needing essential temperature control.

### Packaging



### Heated Enclosures



### Food and Beverage



### Plastic & Rubber Extrusion



### General Heat Processes



## Contact us



**Email:** [Inquiries@West-CS.com](mailto:Inquiries@West-CS.com)  
**Website:** [www.West-CS.com](http://www.West-CS.com)



**Telephone:** +1 800 866 6659  
**Fax:** +1 847 782 5223



**Address:** 1675 Delany Road  
Gurnee  
IL 60031  
USA

BR-MV-1-ENUS-1502