

TEMTRONICS CORP

MG0 INSULATED



1	2	3	5	4	5	7	8	9
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

MIT

CALIBRATION	
J, K, T, E	

1

6

WIRE LENGTH	
EX: 36"	

DIAMETER	
.063	1/16"
.125	1/8"
.188	3/16"
.250	1/4"

2

7

WIRE TYPE	
F	FIBERGLASS
S	FIBERGLASS W/ SSOB
A	FIBERGLASS W/ ARMOR
T	TEFLON
P	PVC

SHEATH MATERIAL	
S	316 SS
I	INCONEL 600

3

8

SHEATH LENGTH	
EX: 6 1/2"	

4

TERMINATION	
A	SPLIT LEADS
B	SPLIT LEADS W/SPADES
C	STANDARD MALE
D	MINI MALE
E	STANDARD FEMALE
F	MINI FEMALE

JUNCTION	
G	GROUNDED
U	UNGROUNDED
E	EXPOSED

5

9

TRANSITION	
S	SPRING
O	NO SRPING

