


TEMTRONICS CORP

MG0 INSULATED



MIT

1	2	3	5	4	5	7	8	9
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

CALIBRATION	
J, JJ, K, KK, T, TT, E, EE	

1

6

WIRE LENGTH	
EX: 42"	

DIAMETER	
1	.063 (1/16")
2	.125 (1/8")
3	.188 (3/16")
4	.250 (1/4")

2

7

WIRE TYPE	
F	FIBERGLASS
S	FIBERGLASS W/ SSOB
A	FIBERGLASS W/ ARMOR
T	TEFLON

SHEATH MATERIAL	
S	316 SS
I	INCONEL 600

3

8

TERMINATION	
A	SPLIT LEADS
B	SPLIT LEADS W/ SPADES
C	STANDARD MALE CONN.
D	MINI MALE CONN.
E	STANDARD FEMALE CONN.
F	MINI FEMALE CONN.

SHEATH LENGTH	
EX: 6 1/2"	

4

9

TRANSITION	
S	SPRING
O	NO SRPING

JUNCTION	
G	GROUNDED
U	UNGROUNDED

5

9

